

Liger © Bus

Regional Transport | Modular + Lightweight





Ligero NG Modular + Lightweight

The Ligero NG is the perfect seat for urban and regional buses: It is the lightest seat of its class - and with the largest possible modularity. Each component is connected with an innovative quick release system. This saves time and money during maintenance and repairs. The fact that the components of the Ligero NG can be replaced individually makes it especially environmentally friendly and robust. The components can also be recycled separately.

As the seating frame of the Ligero NG does not define the height of the back rest, but instead the easily removable back cushion, it is possible to have different back rest heights. The material-saving modular design also has a positive impact on the weight: The Ligero NG weighs around 20 percent less than comparable models, making it the lightest seat in its class - this is also good for the environment, as less weight also means less fuel consumption. The automotive industry served us well for the design of the Ligero NG: The seat resembles that of attractive, comfortable car seats and fits ideally into the ambience of modern urban and regional buses. With regard to covers, numerous different materials are available in addition to artificial and authentic leather, which is even made from recycled materials.





Ligero NG 700

Ligero NG 750

PRODUCT FEATURES AND BENEFITS

- · Lightest seat of its class
- Modular system
- Innovative quick release system
- Environmentally friendly + robust
- Components can be recycled separately



Ligero NG 700 Functions





SEATING SOLUTIONS


Ligero NG 750 Functions






SEATING SOLUTIONS


Ligero NG 700/750 Accessoires






Ligero NG 700 Dimensions








Ligero NG 750 Dimensions







Ligero NG 700/750 Product overview

□ □ □ □ □ 1 □ 1 □ 1 1 1 1 1 1 1 1 1 1 1 1 1	□ □ □ □ □ □ 0 0 0 0 0 0 0 0 0 0 0 0 0 0
□ □ □ 40 mm 90 mm 90 mm • • • • • • • • • • • • • • • • • •	890 mm
□ □ □ 40 mm 90 mm 90 mm • • • • • • • • • • • • • • • • • •	890 mm
40 mm 90 mm n/a n/a n/a n/a	890 mm
40 mm 90 mm n/a n/a n/a n/a n/a	890 mm
40 mm 90 mm n/a n/a n/a n/a n/a	890 mm
90 mm n/a n/a n/a n/a n/a	890 mm
90 mm n/a n/a n/a n/a n/a	890 mm
n/a n/a n/a n/a	
n/a n/a n/a	
n/a n/a n/a	
n/a n/a n/a	
n/a n/a	
n/a n/a	
n/a	
	n/a
. 16.1 kg	ca. 16.5 kg
	ca. 18.5/21 kg
DB	
L	. 16.1 kg

